AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (currently amended) ~~Brush (1) intended to apply, typically onto a support, typically the face, at least one powdered product (9), typically a compacted make-up powder and/or a blusher~~ A brush (1), comprising:

~~including~~ a ~~typically~~ rigid mount ~~M~~ (2), structured as a manual grip for a user,

said mount comprising plural cavities separated from each other,

said mount having a larger dimension less than 50 mm, and a thickness less than 30% of the larger dimension;

~~acting as a means of gripping said brush (1) manually, and a means of applying said product (9) integral with said mount (2) including a typically flexible application material, characterised in that a) said mount M (2) acts as a support to at least two different application means, typically two different tufts T (3, 3') of said application material, with each application means or different tuft T_i~~

at least two tufts (3) configured to apply a powdered product (9) onto a support,

each said tuft including a foot (30) ~~or base B_i (30, 30') so as to anchor each application means to said mount M,~~ and a sheaf (31) of ~~F_i (31, 31') including or constituted by said typically~~ flexible application material,

each sheaf anchored in a corresponding one of the cavities and ~~F_i (31, 31')~~ emerging from a different portion of said mount ~~M~~ along a different surface (20) ~~S_i (20, 20')~~ of said mount,

each sheaf ~~F_i (31, 31')~~ defining a lateral envelope (33) ~~E_i (33, 33')~~ limited at ~~its~~ an envelope end by an application surface (32), ~~A_i (32, 32'), so as typically~~

the application surfaces positioned to simultaneously allow at least two different applications of said powder onto said support with each application surface being free of overlap with any other application surface~~, and in that:~~

~~b) said mount forms a typically two-dimensional object, of larger dimension D typically less than 50 mm, and of thickness E typically less than 0.3 D, in such a way that said brush (1) is able to be placed typically in a make-up case (5)~~.

2. (currently amended) Brush according to claim 1 wherein,

said mount ~~M~~ (2) has a maximum thickness ~~E typically~~ less than 10 mm,

each sheaf ~~F_i having~~ has a length from 50% to 150% of the larger dimension as ~~L_F, said length L_F being~~ taken between said mount ~~M~~ and said application surface ~~A_i, from 0.5.D to 1.5.D~~.

3. (currently amended) Brush according to claim 2 wherein said ~~mount M (2) includes two different tufts T_1 and T_2, each tuft T_1 (3, 4) and T_2 (3', 4') forming a sheaf F_1 (31, 41) and F_2 (31', 41') respectively, emerging from said mount M along~~ ~~two~~ different surfaces are non-planar which respect to each other ~~S_1 (20) and S_2 (20') respectively~~.

4. (currently amended) Brush according to claim 3 wherein,

said different surfaces ~~S_1 (20) and S_2 (20')~~ are longitudinal ~~, typically~~ rectangular or oblong surfaces, of length ~~or larger dimension L typically~~ from 5 to 20 mm [[,]] and of width ~~or smaller dimension l~~ from 1 to 5 mm, with a ratio of the length over the width ~~L/l~~ being from 2 to 10, and ~~so as to form two typically longitudinal~~

the two sheaves are in the form of ~~F_1 and F_2 typically forming~~ two flexible curtains.

5. (currently amended) Brush according to claim [[3]] 1, wherein said surfaces ~~S_1 (20) and S_2 (20')~~ are ~~typically~~

circular[[,]] or semi-circular surfaces, of diameter ~~d typically~~ from 2 to 10 mm.

6. (currently amended) Brush according to claim 1 wherein said different surfaces ~~S_1 (20) and S_2 (20')~~ are contiguous and non-overlapping ~~, on one side or at a common point~~.

7. (currently amended) Brush according to claim 1 wherein each of said different surfaces is free of contact with any adjacent surface ~~S_1 (20) and S_2 (20') are spaced apart by a distance e, measured from edge to edge, or by a distance e', measured from centre to centre, said distance e typically being less than 0.4.D, and e' typically from 0.2.D to 0.8.D~~.

8. (currently amended) Brush according to claim 3 wherein said sheaves ~~F_1 (31, 31', 41, 41')~~ have a maximum angle of aperture $\alpha>0$ and possibly a minimum angle of aperture $\alpha'>0$, with $\alpha'<\alpha$ and wherein said surfaces ~~S_1 (20) and S_2 (20')~~ are non-contiguous and are spaced apart by a distance e such that said corresponding application surfaces ~~A_1 (32, 42) and A_2 (32', 42')~~ are contiguous, given said angle of aperture α and said distances e or e'.

9. (currently amended) Brush according to claim 3 wherein said sheaves ~~F_i (31, 31', 41, 41')~~ have a maximum angle of aperture $\alpha>0$ and ~~possibly~~ a minimum angle of aperture $\alpha'>0$, with $\alpha'<\alpha$ and wherein said surfaces ~~S_1 (20) and S_2 (20')~~ are non-contiguous and are spaced apart by a distance e such that said corresponding application surfaces ~~A_1 (32, 42) and A_2 (32', 42')~~ are non-contiguous, given said angle of aperture α and said distances e or e'.

10. (currently amended) Brush according to claim 3 wherein said surfaces ~~S_1 (20) and S_2 (20')~~ are in one and the same plane ~~P'~~ which is ~~typically~~ perpendicular to ~~said~~ a medium plane ~~P~~.

11. (currently amended) Brush according to claim 3 wherein said surfaces ~~S_1 (20) and S_2 (20')~~ are in different planes and ~~P'_1 and P'_2 respectively, typically~~ perpendicular to ~~said~~ a medium plane P, and forming between them an angle β~~,~~ ~~typically~~ equal to $150°\pm25°$, in such a way that, with said corresponding application surfaces ~~A_1 (32, 42) and A_2 (32', 42')~~ forming between them an angle typically close to said angle β, said application surfaces are able to conform in shape to the outlines and contours of the face, typically the cheekbones of the face.

12. (currently amended) Brush according to claim 11 wherein at least one of the planes ~~P'_1 and P'_2~~ is not perpendicular to said medium plane ~~P~~.

13. (currently amended) Brush according to claim 2 wherein said different tufts ~~T_1 (3, 4) and T_2 (3', 4')~~ are geometrically symmetrical relative to a plane of symmetry ~~Ps perpendicular to said plane P~~.

14. (currently amended) Brush according to claim 2 wherein said different tufts ~~T_1 (3, 4) and T_2 (3', 4')~~ are tufts of hair (4, 4') constituted by hairs ~~PL~~ of the same nature or texture.

15. (currently amended) Brush according to claim 2 wherein said different tufts ~~T_1 (3, 4) and T_2 (3', 4')~~ are tufts of hair (4, 4') constituted by hairs of different nature or texture ~~PL1 and PL2~~, so as to be able to form two applications, different by texture or grain, of one and the same product or of two products.

16. (currently amended) Brush according to claim 2 wherein said different tufts ~~T_1 (3, 4) and T_2 (3', 4')~~ are formed by one and the same fibrous or alveolar material able to provide

a transfer of said product, or by two different fibrous or alveolar materials able to provide a transfer of said product.

17. (currently amended) Brush according to claim 13 wherein said application surfaces ~~A_1 (32, 42) and A_2 (32', 42')~~ project themselves orthogonally over a plane ~~Pp~~ perpendicular to said plane <u>of symmetry</u> ~~Ps typically according to a rectangle S_A of length L_A and of width l_A, each application surface (32, 32', 42, 42') projecting itself typically along a length $L_A/2$, in the case of contiguous application surfaces A_1 and A_2, with L_A typically less than D and with l_A typically less than 3.E~~.

18. (cancelled)

19. (currently amended) Brush according to claim 1 wherein said foot ~~or base B_i~~ of each tuft T_i is anchored~~, typically~~ by bonding~~, to said surface S_i of said mount (2)~~.

20. (currently amended) <u>Brush according to claim 1 in combination with a case</u> ~~Case (5)~~ for dispensing product ~~typically~~ in the form of compacted powder (9) ~~including a brush (1) according to claim 1~~, said brush (1) ~~forming a means of application of said product and being of dimensions adapted to those of said case, so as~~ to be able to be placed in said closed case (5) between a bottom (6) of said case fitted with at least

one pot (8) containing said compacted powder (9) and a lid (7) of said case ~~typically~~ including a mirror (70).

21. (currently amended) ~~Case~~ Combination according to claim 20 including a single pot (8) containing a single compacted product ~~PC~~ and wherein the compacted product has a contact surface S_C with a dimension or width L_C such that the ratio L_A/L_C is ~~close to 1 and typically~~ between 0.7 and 1.1, so as to apply the same product using two different tufts ~~T_1 and T_2~~ of said brush.

22. (currently amended) ~~Case~~ Combination according to claim 20 wherein said compacted product (9) includes two different compacted products ~~PC_1 and PC_2 typically~~ forming a single block of compacted powder, and separated along a typically straight line of demarcation ~~LD~~, so that, said brush being applied against said compacted product and said central common area ~~ZC~~ of said tufts along said line of demarcation ~~LD, it is thus possible~~ to take up simultaneously two different products typically in a single movement.

23. (currently amended) ~~Case~~ Combination according to claim 20 wherein each of said two different compacted products ~~PC_1 and PC_2~~ forms a block placed in one and the same pot (8) or in two pots (8, 8') side by side along a line of demarcation ~~LD'~~,

in such a way that the two blocks are ~~typically~~ 2 mm apart at the most.

24. (currently amended) ~~Case~~ Combination according to claim 22 wherein said compacted products ~~PC1 and PC2~~ have a total contact surface ~~S_e~~ with an average dimension L_C, taken perpendicularly to said line of demarcation ~~LD or LD'~~ comparable to a straight portion, such that the ratio L_A/L_C is ~~close to 1 and typically~~ between 0.7 and 1.1, so as to have a contact surface ~~S_e~~ adapted to said brush (1).

25. (currently amended) ~~Case~~ Combination according to claim 20 wherein said contact surface ~~S_e~~ forms an angle γ ~~typically~~ close to 180°±40° ~~or possibly 360°-β~~, in such a way that said brush, according to the geometric shape of said application surface ~~A_1 or A_2~~, is able to take up powder from said two products uniformly by passing said sheaves of hair ~~F_1 and F_2~~ over said contact surface ~~S_e~~.